

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 August 2002 (29.08.2002)

PCT

(10) International Publication Number
WO 02/067294 A3

(51) International Patent Classification: **H01L 21/00**

(21) International Application Number: **PCT/EP02/01408**

(22) International Filing Date: **11 February 2002 (11.02.2002)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
01103989.8 **19 February 2001 (19.02.2001)** **EP**

(71) Applicants (for all designated States except US): **INFINEON TECHNOLOGIES AG [DE/DE]; St.-Martin-Str. 53, 81669 München (DE). INFINEON TECHNOLOGIES SC300 GMBH & CO. KG [DE/DE]; Königsbrücker Str. 180, 01099 Dresden (DE). MOTOROLA INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).**

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HIATT, Mark [US/DE]; Ludwig-Hartmann-Str. 3, 01277 Dresden (DE). MAUTZ, Karl [US/US]; c/o Motorola Inc., Patent Dept. AU934, 7700 Parmer LN W. Austin, TX 78729 (US). SCHUSTER, Ralf [DE/DE]; Alaunstr. 91a, 01099 Dresden (DE).**

(74) Agents: **EPHING, HERMANN & FISCHER et al.; Rindlerstr. 55, 80339 München (DE).**

(81) Designated States (national): **JP, KR, SG, US.**


Published:

— with international search report

(88) Date of publication of the international search report:
12 December 2002

[Continued on next page]

(54) Title: **ARRANGEMENT AND A METHOD FOR REDUCING CONTAMINATION WITH PARTICLES ON A SUBSTRATE IN A PROCESS TOOL**



(57) Abstract: A process tool (2), preferably a spin coater, comprises a set of at least three arms (5) and an adjustable rinse nozzle (7). The arms (5) lift a substrate (1), e.g. a semiconductor wafer, from a chuck (4) inside the process chamber (3) after having performed the corresponding manufacturing step, e.g. coating. The contact area between the arms and the substrate (1) is as small as possible. The rinse nozzle (7) dispenses a solvent liquid (10) onto the backside (1b) of the substrate (1), thereby removing contaminating particles assembling at the position of the contact area of vacuum channels (23) of the chuck (4) with the substrate (1). The set of arms (5) rotates for a homogeneous cleaning. A gas outflow out of vacuum ports (24) of the chuck prevents an obstruction of the vacuum ports (24) with particles. While the substrate (1) is being lifted, the chuck (4) can also be cleaned by dispensing said solvent liquid (10) onto said chuck (4).

WO 02/067294 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Docket # P2001,0110

Applic. # _____

Applicant: Mark Hiatt et al.

Lerner and Greenberg, P.A.
Post Office Box 2480
Hollywood, FL 33022-2480
Tel: (954) 925-1100 Fax: (954) 925-1101